

REDETEX

Ready Mix Texture

Professional Benefits

Quicker to mix than bag texture

Superior profile and pattern to joint compound

Less overspray when compared to joint compound

Low shrinkage

Freeman **RedETex Ready-Mix Texture** is a non-aggregated, ready mixed product formulated to produce a uniform texture on interior walls and ceilings. **RedETex** may be applied to interior gypsum board, plaster, or concrete surfaces and is especially designed to hide or cover minor surface irregularities. **RedETex** is used to create a variety of decorative texture finishes.



QUALITY DRYWALL PRODUCTS

REDETEX

Ready Mix Texture

Delivery and Storage of materials: All materials shall be delivered in the manufacturer's original, unopened, undamaged containers with identification labels intact. Store material in a protected area not exposed to extremes in temperature or humidity. Do not store in direct sunlight. Keep product from freezing.

Environmental Conditions: During application of gypsum board, joint finishing, and decorating a constant temperature above 50 F and below 100 F must be maintained before, during and after installation. Provide adequate ventilation, allow product dry completely.

Mixing: Mix with a mechanical mixer. If additional water is needed for the desired application add only cool, clean potable water in small amounts and mix, repeat if necessary. Avoid over mixing and over thinning. Do not mix with any other product.

Application: Surface preparation: Finish gypsum wallboard surface to a minimum of a level 3 finish as described by the Gypsum Association in GA-214-2015 Recommended Levels of Finish for Gypsum Board, Glass Mat & Fiber-Reinforced Gypsum Panels. Prior to application the entire surface must be clean, dry, free of dust or dirt, grease, and any water soluble materials. A coat of drywall primer such as Freeman 555 Gypsum Board Primer is recommended to equalize the porosity across the gypsum board and joint compound – this will reduce or eliminate the potential for flashing over joints and increase bond. Once all prior applications (primer, cornerbead, fasteners, joints) are completely dry and the surface is clean the texture may be applied.

Application: May be applied with brush, roller, airless-sprayer, or piston or stator-type pump. Allow

to dry completely before proceeding to next stage. Maintain a minimum of 50 F air and surface temperature during and following application until completely dry.

Coverage: Texture coverage is highly dependent on the viscosity of the product, method of application, and the texture type. 350-700 sq. ft. is an estimated coverage rate.

Cleanup: Clean all tools, equipment, and skin with soapy water and rinse thoroughly with clean water. Clean all drips and spills immediately with a damp cloth. On unfinished floors wait until any overspray is dry and use a floor scraper.

Sanding: Always use a NIOSH/MSHA approved respirator, eye protection, and cover exposed areas of skin. If sanding is required dry sanding may be used but a wet sanding method is recommended to reduce dust. Provide adequate ventilation.

Decorating: RedETex is not recommended as the final decoration and should be painted. Product is non-washable.

Always follow the manufacturer's instructions for all decorative finishes (paint etc.)

Product Data: Color: White to off white
Shelf life: 6 months under normal storage conditions
Packaging: 50lb cardboard cartons

For a complete copy of warranty information contact:
Freeman Products, Inc. 1-800-364-2763