

ONETEX 2000

Base Coat & Texture

Professional Benefits Mold and Mildew Resistant

Washable

Durable surface

No Paint Chipping – Color is all the way through

OneTex 2000 has been formulated for use over interior plaster and drywall surfaces. The outstanding combination of pigments and resin has yielded excellent results on jobs where good scrub resistance and economy are of prime importance.



QUALITY DRYWALL PRODUCTS

ONETEX 2000

Base Coat & Texture

Surface Preparation: Surfaces must be clean, dry, and free of grease, wax, and gloss.

Mixing and Thinning: If thinning is necessary, thin with water. Do not exceed one pint of water per five gallons of product! Caution: Do not over mix.

Application and Coverage: Apply OneTex 2000 with an airless-sprayer, or conventional spray machine. Room temperature must be 50 degrees F (10°C) for applying OneTex. OneTex coating is designed to cover approximately 100 to 125 sq. ft. per gallon.

Equipment Cleaning: Clean equipment with warm soapy water. Rinse with tap water.

Colors: Available in pastels and off whites.

Limited Warranty: OneTex 2000 will cover similar colors in one coat when applied at 100 to 125 sq. ft. per gallon and when applied in accordance to label instructions. OneTex will perform as follows for a period of 1 year:

1. Fade Resistant - will retain color
2. Spot Resistant - spots from water, soap, or detergent can washed off.
3. Washable - when washing instructions are followed, normal dirt deposits can be washed off. Use sponge dampened in soapy water for best results.

If OneTex fails to perform as specified, when applied according to label instructions, OneTex's obligation shall be limited to refund of purchase price. Sales slips must accompany evidence of failure. For a complete copy of warranty call: 1-800-364-2763.

Caution: This product may cause skin sensitivity. When applying by sprayer use respirator approved by the NIOSH. If exposed, wash with soap and water thoroughly. Harmful if taken internally. Keep out of reach of children. For a copy of MSDS call: 1-800-364-2763.

Product Data:

Type of Pigment: Titanium Dioxide
Aluminum Silicate
Calcium Carbonate

Type of Vehicle: Acrylic

Solvent Thinner: Water, Ethylene Glycol

Clean Up & Thinner: Water

Packaging: 5 Gal. Plastic Pail

% Solids by Weight: 66

% Solids by Volume: 46

Weight per Gallon: 11.6 lbs

Pigment Volume Concentration (PVC): 70%

For a complete copy of warranty information contact:
Freeman Products, Inc. 1-800-364-2763