

# Splatter Texture

---

FREEMAN SPLATTER TEXTURE is a non-aggregated Non-Asbestos dry powder that when mixed with water allows for a variety of different texture effects. Some common texture designs are orange peel, crows foot, splatter and splatter knockdown. Texture may be used on walls and ceilings. Not a color specified product and must be coated with a paint product. Texture is not washable unpainted.

## *Professional Benefits*

### High Profile Pattern

---

### Outstanding Open Time

---

### Superior Mileage To ready Mix

#### **Delivery and Storage of Materials:**

All materials shall be delivered in the original unopened containers. Do not expose to elements or extremes in temperature or humidity. Do not store in direct sunlight. Do not expose to moisture. Protect from freezing after mixing with water.

#### **Environmental Conditions:**

During application of gypsum board, joint finishing and decorating minimum temperatures of air and surface above 50' F must be maintained. Temperature and ventilation must be maintained during application and until completely dry. Protect from freezing.

#### **Mixing:**

Place approximately two (2) gallons of clean, potable water in a clean container. Gradually, add contents of bag of texture to the water, stirring vigorously while adding the powder. Mix thoroughly with a mechanical mixer until no lumps are present. Allow to stand for about five minutes and stir again. Add additional water if required to achieve the consistency for the desired texture effect. Avoid over mixing and over thinning

#### **Application:**

May be applied with a large wall brush and roller, with a trowel, a hopper type spray machine or texture spray machine. A combination of these may also be used to achieve the desired texture pattern.

#### **Coverage:**

Normal spreading rate 250-400 square feet per 25 lb. bag, depending on the type of surface applied over and the desired texture effect.

#### **Cleanup:**

Clean all tools, equipment and skin with soapy water and rinse with clean water. Clean all drips and spills immediately with a damp cloth.

#### **Sanding:**

Wet sanding or sponging is recommended. If dusty use NIOSH approved respirator for nuisance dust, safety glasses and protective clothing to cover exposed areas of body. Reduce dust by ventilation and/or use of vacuum sander. Provide adequate ventilation.

#### **Decorating:**

When painting or decorating follow manufacturer's instructions.



QUALITY DRYWALL PRODUCTS

# Splatter Texture Submittal

---

Compliance with Standards:  
Meets or exceeds ASTM C475

Material:  
Dry powder vinyl and/or starch formulation.

Freezing Sensitivity:  
Protect from freezing after mixing with water, during application and until completely dry.

Storage:  
Rotate stock, estimated shelf life one (1) year under good conditions. Protect from extremes in temperature and humidity. Do not store in direct sunlight. Do not allow to freeze after mixing.

Packaging:  
Available in 50 lb. (22.65 Kg) Bag.

## HEALTH HAZARD CAUTIONS

**AVOID BREATHING DUST.** May contain Mica, Talc, Silicates, Calcium Carbonate. Long term inhalation of dust may cause chronic respiratory problems.

**WHEN MIXING** wear NIOSH mask for nuisance dust and safety glasses.

**WHEN SPRAYING** wear NIOSH mask for vapors, protective clothing over body and safety glasses.

### **Danger**

May cause cancer (Inhalation): May cause damage to organs (lung, kidneys) through prolonged or repeated exposure (Inhalation)

Obtain special instructions before use: Do not handle until all safety precautions have been read and understood: Do not breathe dust: Wear appropriate PPE: If exposed or concerned: Get medical advice/attention: Get medical advice/attention if you feel unwell: Store locked up: Dispose of contents/container to comply with local/regional/national/international regulations

**ASBESTOS FREE**

May Contain Mica, Talc, Calcium Carbonate and/or other silicates



**DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN**

## **Submittal Approval**

Job Name: \_\_\_\_\_

Contractor: \_\_\_\_\_

Date: \_\_\_\_\_

For a complete copy of warranty information contact:  
**Freeman Products, Inc. 1-800-364-2763**